

www.tmmanterola.com

Tips for installation, use and maintenance



TECHNICAL SPECIFICATIONS

C = 340

PRODUCT "MATERIALS "MA



- 2 PLUG & SHAFT CW617N brass, according to EN 12164.
- **3 SEAT'S PLUG PTFE** suitable for contact with drinking water.
- O PLUG SEAL FPM.

Nickel-Plated brass.




NOMINAL PRESSURE *30 bar* (*PN-30*).

MAXIMUM TEMPERATURE 150°C. MINIMUM TEMPERATURE 0°C.

Water starts to flow at a pressure of 0.5 bar.

NOTE: All materials used to manufacture these valves are suitable for contact with water intended for human consumption.

MAIN DIMENSIONS



| | | | Dimensions [mm] | |
|---------|-----------|----|--------------------|-----|
| Ref. | Measure R | DN | Р | L |
| 0501200 | 3/8" | 10 | 11 | 55 |
| 0501201 | 1/2" | 15 | 14,5 | 55 |
| 0501202 | 3/4" | 20 | 19 | 63 |
| 0501203 | 1" | 25 | 23 | 70 |
| 0501204 | 1, 1/4" | 32 | 31 | 75 |
| 0501205 | 1, 1/2" | 40 | 38 | 83 |
| 0501206 | 2 | 50 | 48 | 90 |
| 0501207 | 2, 1/2" | 65 | 62 | 120 |
| 0501208 | 3" | 80 | 73 | 127 |